

GT Series Glazing Tape is used to seal glass into wood, aluminum and vinyl frames. Closed cell foam seals against air, moisture, dust and light penetration while serving to fill any irregularities in the sash extrusion. Our GT Series Glazing Tape also provides cushioning, vibration and shock absorption, thermal insulation, and sound deadening properties. This product also features good UV resistance. AAMA* tested and approved by an independent testing lab.

Technical Specifications				
Physical Property	U/M	Test Method	Value	Notes
Application Temperature	F		50	Min.
Color		*	Black and White	
Compression Deflection	PSI	AAMA 2.14 Test A	5.5	
Compression Deflection	PSI	AAMA 2.14 Test B	4.6	
Compression Set	%	AAMA 2.15	3.5	
Low Temp. Flexibility		AAMA 2.9.3	No Cracking	
Maximum Temperature	F		220	
Minimum Temperature	F		-30	
Peel Adhesion	PIW	AAMA 2.20 @ 32 F	12.2	Aluminum
Peel Adhesion	PIW	AAMA 2.20 @ 32 F	13.7	Glass
Peel Adhesion		PSTC #3	N/A	No peel. Adhesive strength greater than the internal strength of the foam.
Pump Test		AAMA 2.18	-	No Displacement, No Seal Loss, No Delamination, No Cracking
Static Shear		PSTC #7	7+ Days, No Creep	500 gms/sq. in. @ 70F, no dwell to stainless steel
Tensile Adhesion	%	AAMA 2.19 @32 F	300	@ 77.7 psi
Tensile Adhesion	%	AAMA 2.19 @ 77 F	150	@ 43.2 psi
Tensile Adhesion	%	AAMA 2.19 @ 120 F	110	@ 35.7 psi
Thickness			.03", .06", .125"	
Thickness	%	AAMA 2.16	0.5	
Water Penetration	%	AAMA 2.17	0.0	

*American Architectural Manufacturing Association (AAMA) 810.1-91 for Expanded Cellular Glazing Tape, Type 1.