

# Specifications

- Closed-Cell, Cross-Linked PE Foam with Acrylic Adhesive both sides
- AAMA 810.1-16 for Expanded Cellular Glazing Tape
- White in color with a Blue Poly Liner
- 1/16" thick: cut to your width
- Seals Window Glass to multiple substrates including Wood, Aluminum and Plastic
- Seals against Air, Moisture, Light and Dust
- Provides cushioning to absorb vibration and shock
- Provides thermal insulating and sound deadening

# Physical Properties

Physical Property	Test Method	Unit	Value
Compression Deflection	AAMA 810.1 Type 1	kPa	60.6
Low Temperature Flexibility	AAMA 810.1 Type 1		No Cracking
Compression Set	AAMA 810.1 Type 1	%	4
Water Absorption	AAMA 810.1 Type 1	%	7 max
Water Penetration	AAMA 810.1 Type 1	%	0
Tensile Adhesion: @ 25°C @ 50°C @0°C	AAMA 810.1 Type 1		186% - 34 kPa 192% - 328 kPa 200% - 454 kPa
Peel Adhesion: @ 0°C Glass @ 0° C Alum. @ 50°C Glass @ 50°C Alum.	AAMA 810.1 Type 1	N/mm	8.98 11.11 8.96 9.68

PLEASE NOTE THAT ALL DATA SHEETS ARE SUPPLIED BY LAMATEK, INC. WITH THE UNDERSTANDING THAT THE PURCHASER MUST DETERMINE THE SUITABILITY OF A PARTICULAR PRODUCT FOR ITS INTENDED PURPOSE. UNLESS OTHERWISE STATED, LAMATEK, INC. CANNOT WARRANT PRODUCTS IN THEIR APPLICATION.